





<b>i</b>	<b>Power pack +5 V / 25 W</b>															
Power pack +5 V / 25 W Item no. 420178	Compact switch mode power pack +5 V / 25 W with international approval															
	Technical Data	<table border="1"> <tr> <td>Input voltage:</td> <td>AC 100 – 240 V (Wide Range), 47–63 Hz</td> </tr> <tr> <td>Output voltage</td> <td>DC 5.1 V</td> </tr> <tr> <td>Output voltage:</td> <td>5 A (continuous)</td> </tr> <tr> <td>Approvals:</td> <td>UL, EN, CSA, CB</td> </tr> <tr> <td>Dimensions (WxHxD):</td> <td>45 × 75 × 91 mm</td> </tr> <tr> <td>Weight:</td> <td>240 g</td> </tr> <tr> <td>Assembly:</td> <td>On the 35 mm wide DIN mounting rail</td> </tr> </table>	Input voltage:	AC 100 – 240 V (Wide Range), 47–63 Hz	Output voltage	DC 5.1 V	Output voltage:	5 A (continuous)	Approvals:	UL, EN, CSA, CB	Dimensions (WxHxD):	45 × 75 × 91 mm	Weight:	240 g	Assembly:	On the 35 mm wide DIN mounting rail
Input voltage:	AC 100 – 240 V (Wide Range), 47–63 Hz															
Output voltage	DC 5.1 V															
Output voltage:	5 A (continuous)															
Approvals:	UL, EN, CSA, CB															
Dimensions (WxHxD):	45 × 75 × 91 mm															
Weight:	240 g															
Assembly:	On the 35 mm wide DIN mounting rail															

<b>i</b>	<b>Power pack +24 V / 50 W</b>															
Power pack +24 V / 50 W Item no. 420179	Compact switch mode power pack +24 V / 50 W with international approval															
	Technical Data	<table border="1"> <tr> <td>Input voltage:</td> <td>AC 100 – 240 V (Wide Range), 47–63 Hz</td> </tr> <tr> <td>Output voltage</td> <td>DC 24 V</td> </tr> <tr> <td>Output voltage:</td> <td>2.1 A (continuous)</td> </tr> <tr> <td>Approvals:</td> <td>UL, EN, CSA, CB</td> </tr> <tr> <td>Dimensions (WxHxD):</td> <td>45 × 75 × 91 mm</td> </tr> <tr> <td>Weight:</td> <td>240 g</td> </tr> <tr> <td>Assembly:</td> <td>On the 35 mm wide DIN mounting rail</td> </tr> </table>	Input voltage:	AC 100 – 240 V (Wide Range), 47–63 Hz	Output voltage	DC 24 V	Output voltage:	2.1 A (continuous)	Approvals:	UL, EN, CSA, CB	Dimensions (WxHxD):	45 × 75 × 91 mm	Weight:	240 g	Assembly:	On the 35 mm wide DIN mounting rail
Input voltage:	AC 100 – 240 V (Wide Range), 47–63 Hz															
Output voltage	DC 24 V															
Output voltage:	2.1 A (continuous)															
Approvals:	UL, EN, CSA, CB															
Dimensions (WxHxD):	45 × 75 × 91 mm															
Weight:	240 g															
Assembly:	On the 35 mm wide DIN mounting rail															

<b>i</b>	<b>Power pack +24 V / 100 W</b>															
Power pack +24 V / 100 W Item no. 420211	Compact switch mode power pack unit +24 V / 100 W with international approval															
	Technical Data	<table border="1"> <tr> <td>Input voltage:</td> <td>AC 100 – 120 V / 220 – 240 V (Auto Select), 47–63 Hz</td> </tr> <tr> <td>Output voltage</td> <td>DC 24 V</td> </tr> <tr> <td>Output voltage:</td> <td>4.2 A (continuous)</td> </tr> <tr> <td>Approvals:</td> <td>UL, EN, CSA, CB</td> </tr> <tr> <td>Dimensions (WxHxD):</td> <td>73 × 75 × 103 mm</td> </tr> <tr> <td>Weight:</td> <td>360 g</td> </tr> <tr> <td>Assembly:</td> <td>On the 35 mm wide DIN mounting rail</td> </tr> </table>	Input voltage:	AC 100 – 120 V / 220 – 240 V (Auto Select), 47–63 Hz	Output voltage	DC 24 V	Output voltage:	4.2 A (continuous)	Approvals:	UL, EN, CSA, CB	Dimensions (WxHxD):	73 × 75 × 103 mm	Weight:	360 g	Assembly:	On the 35 mm wide DIN mounting rail
Input voltage:	AC 100 – 120 V / 220 – 240 V (Auto Select), 47–63 Hz															
Output voltage	DC 24 V															
Output voltage:	4.2 A (continuous)															
Approvals:	UL, EN, CSA, CB															
Dimensions (WxHxD):	73 × 75 × 103 mm															
Weight:	360 g															
Assembly:	On the 35 mm wide DIN mounting rail															

<b>i</b>	<b>Power pack +48 V / 240 W</b>															
Power pack +48 V / 240 W Item no. 420227	Compact and feedback protected switch mode power pack +48 V / 240 W with active PFC and international approval															
	Technical Data	<table border="1"> <tr> <td>Input voltage:</td> <td>AC 100 – 240 V (Wide Range), 47–63 Hz</td> </tr> <tr> <td>Output voltage</td> <td>DC 48 V</td> </tr> <tr> <td>Output voltage:</td> <td>5 A (continuous)</td> </tr> <tr> <td>Approvals:</td> <td>UL, EN, CSA, CB</td> </tr> <tr> <td>Dimensions (WxHxD):</td> <td>60 × 124 × 117 mm</td> </tr> <tr> <td>Weight:</td> <td>900 g</td> </tr> <tr> <td>Assembly:</td> <td>On the 35 mm wide DIN mounting rail</td> </tr> </table>	Input voltage:	AC 100 – 240 V (Wide Range), 47–63 Hz	Output voltage	DC 48 V	Output voltage:	5 A (continuous)	Approvals:	UL, EN, CSA, CB	Dimensions (WxHxD):	60 × 124 × 117 mm	Weight:	900 g	Assembly:	On the 35 mm wide DIN mounting rail
Input voltage:	AC 100 – 240 V (Wide Range), 47–63 Hz															
Output voltage	DC 48 V															
Output voltage:	5 A (continuous)															
Approvals:	UL, EN, CSA, CB															
Dimensions (WxHxD):	60 × 124 × 117 mm															
Weight:	900 g															
Assembly:	On the 35 mm wide DIN mounting rail															